

DIMENSIONS

LENGTH

1,900 mm

WIDTH

KS 475: 3,490 mm

KS 490: 4,010 mm

HEIGHT

1,450 mm (transporting position)

BASIC MACHINE EMPTY WEIGHT

KS 475: 1,150 kg

KS 490: 1,300 kg

WORKING WIDTH

NUMBER OF ROWS

4

ROW WIDTH

KS 475: 750 / 800 mm

KS 490: 850 / 900 mm

DRIVE & TOPPER SHAFT

INPUT SPEED

540 / 750 / 1,000 rpm

POWER TRANSMISSION

KS 475: single side drive with 4 V-belts
KS 490: bilateral side drive with 4 V-belts

FREEWHEEL IN THE DRIVE TRAIN

yes

COUNTER BLADE

yes

HAULM DISCHARGE

Integral haulm discharge

SUPPORT WHEELS

NUMBER

2 pieces

TYRES

185/65 R14

COUPLING AND TRANSPORT POSITION

MOUNTING TYPE

3-point front and rear mounting

3-POINT ATTACHMENT

Cat. 2

ROAD TRAVEL

3-point attachment or optional end tow kit

HEIGHT ADJUSTMENT

Spindle + lower guide rod

REQUIREMENTS FOR TRACTOR

MINIMUM ENGINE POWER

KS 475: 50 kW

KS 490: 55 kW

OPTIONAL EQUIPMENT

STANDARD

3-point attachment for front or rear mounting
Variably adjustable track width of the support wheels
Wide-angle cardan shaft (double)
Side drive 4 V-belts
Freewheel in the drive train
Height adjustment via spindle and lower guide rod
Integrated counter blade
Integral haulm discharge

ADDITIONAL EQUIPMENT:

Trailing press wheels
End tow kit
Lighting and warning signs
Swing support wheels